

Konfigurasi Apache MPM Prefork + PHP (mod_php)

1 Nonaktifkan PHP-FPM

```
sudo systemctl stop php8.1-fpm
sudo systemctl disable php8.1-fpm
```

Nonaktifkan konfigurasi Apache FPM:

```
sudo a2disconf php8.1-fpm
sudo a2dismod proxy_fcgi
```

2 Aktifkan MPM Prefork

Matikan MPM Event:

```
sudo a2dismod mpm_event
```

Aktifkan Prefork:

```
sudo a2enmod mpm_prefork
```

3 Pastikan **mod_php** sesuai versi **PHP** terpasang:

```
sudo apt install libapache2-mod-php8.1
```

```
sudo a2enmod php8.1
```

4 Restart Apache Prefork

```
sudo systemctl restart php81.-fpm
```

```
sudo systemctl restart apache2
```

5 Cek MPM:

```
apachectl -V | grep -i mpm
```

Harus muncul:

Server MPM: prefork

6 □ Optimasi Prefork

```
sudo nano /etc/apache2/mods-available/mpm_prefork.conf
```

```
<IfModule mpm_prefork_module>  
  StartServers      5  
  MinSpareServers   5  
  MaxSpareServers   10  
  MaxRequestWorkers 150  
  MaxConnectionsPerChild 3000  
</IfModule>
```

```
sudo systemctl restart apache2
```

Revisi #2

Dibuat 24 Desember 2025 01:21:44 oleh Friscia Anthony

Diperbaharui 24 Desember 2025 01:27:53 oleh Friscia Anthony